



OTHO SERIES

TECHNICAL SPECIFICATIONS

MODEL	WORKING WIDTH	DISCS	BEARINGS	CATEGORY	ROWBAR POWER	DISCS 20"/510x6mm.> 24"/610x6mm.	
						WEIGHT APPROX. NON STOP	WEIGHT APPROX. SILENT BLOCK
"GR RH"	M.	Nº	Nº		HP/CV	Kg.	Kg.
GR - RH400 - 32	4,00	32	16	III	160-180	3500	3240
GR - RH450 - 36	4,50	36	18	III	180-200	3650	3420
GR - RH500 - 40	5,00	40	20	III	200-220	3900	3600
GR - RH550 - 44	5,50	44	22	III	220-240	4150	3800
GR - RH600 - 48	6,00	48	24	III	240-260	4400	4000
GR - RH720 - 60	7,20	60	30	DRAW BAR	250-300	8200	-

FRAME SECTION: 100x100x8 mm.
DISCS: 20"/510x6mm.> 24"/610x6mm.
DISCS AXLE: 40 mm.
ROWS SPACING: 950 mm.
FRAME CLEARANCE: 670 mm.
DEPTH MAX.: 5-15 mm.
TRANSPORT WIDTH: 3,00 m.
TRANSPORT KIT: Option



Gascón International
 Herederos de Manuel Gascón S.L.
 Tel. +34-974-21 87 20
 Fax. +34-974-21 87 21

info@gasconinternational.com

INTERNATIONAL OFFICES
 Tel. +34-689 82 30 51
 Tel.Fax. +34-93-783 87 93

export@gasconinternational.com



OTHO SERIES

TECHNICAL SPECIFICATIONS

MODEL	WORKING WIDTH	TRANSPORT WIDTH	DISCS		BEARINGS	CATEGORY	ROWBAR POWER	DISCS 20"/510x6mm.> 24"/610x6mm.	
			Nº	Nº				WEIGHT APPROX. NON STOP	WEIGHT APPROX. SILENT BLOCK
"GR RF"	M.	M.				HP/CV	Kg.	Kg.	
GR - RF250 - 20	2,50	2500	20	10	II	100-120	1700	1580	
GR - RF300 - 24	3,00	3000	24	12	II	120-140	1950	1800	
GR - RF350 - 28	3,50	3500	28	14	II	140-160	2200	2030	
GR - RF400 - 32	4,00	4000	32	16	II-III	160-180	2500	2310	

FRAME SECTION: 100x100x8 mm.
DISCS: 20"/510x6mm.> 24"/610x6mm.
DISCS AXLE: 40 mm.
ROWS SPACING: 950 mm.
FRAME CLEARANCE: 670 mm.
DEPTH MAX.: 5-15 mm.



Gascón International
 Herederos de Manuel Gascón S.L.
 Tel. +34-974-21 87 20
 Fax. +34-974-21 87 21

info@gasconinternational.com

INTERNATIONAL OFFICES
 Tel. +34-689 82 30 51
 Tel.Fax. +34-93-783 87 93

export@gasconinternational.com