

KER SERIES

TECHNICAL SPECIFICATIONS

MODEL	WORKING WIDTH	TRANSPORT WIDTH	CAPACITY	CATEGORY	TYRES	ROWBAR POWER	WEIGHT APPROX.
MOUNTED	M.	mm.	m3			HP/CV	Kg.
TS 5	1,00	1200	0,50	I	4.00 R8	30-40	300
TS 8	1,40	1600	0,80	I-II	6.00 R9	45-55	500
CARRIED HYDRAULIC							
TV1	1,26	1500	1,00	-	6.00-16	40-50	800
TV5	1,81	2050	1,50	-	7.00-16	55-65	900
HYDRAULIC DISCHARGE							
TH2500	2,22	2550	2,50	-	265/70 R19.5	70-80	1650
TH3000	2,22	2550	3,00	-	265/70 R19.5	80-90	1700
TH3500	2,35	2650	3,50	-	285/70 R19.5	90-100	1850
TH4000	2,40	2800	4,00	-	385/65 R22.5	100-120	2500
TH4500	2,20	2550	4,50	-	385/65 R22.5	120-130	2800
TH5000	2,50	2900	5,00	-	385/65 R22.5	130-150	3000

GATE OPENING:

MECANIC

DISCHARGE:

HYDRAULIC: MODELS TH4500 & TH5000. NECESSARY 3 DOUBLE EFFECT WAYS

MECANIC: MODEL "TS"

HYDRAULIC: MODELS "TV" & "TH";

CUCHILLAS:

HARDOX: MODEL "TH"

LUCES DE SEÑALIZACIÓN:

ALL MODELS

TS:

Ideal for vineyards and orchards

TV:

Ideal for vineyards and orchards

TH:

Ideal for agricultural and civil use

