



# AKER SERIES

## TECHNICAL SPECIFICATIONS

MODEL	WORKING WIDTH	TINES	TINES SECTION	TINES SPACING	FRAME SECTION	DEPTH MAX.	FRAME CLEARANCE	ROWBAR POWER	LINKAGE CATEGORY	ROLLER	WEIGHT WITHOUT ROLLER	WEIGHT WITH ROLLER
	M.	Nº	mm.	mm.	mm.	mm.	mm.	HP/CV		Ø	Kg.	Kg.
SS1N	1,00	1	30x155	-	180x100x8	450	740	30/50	I	-	150	-
SS3N - SS3NR	1,40	3	30x155	600	230x100x8	450	740	40/60	II	Ø 470	280	350
SS5L - SS5LR	2,00	5	30x155	400	230x100x8	450	740	60/70	II	Ø 470	420	525
SS5N - SS5NR	2,20	5	35x155	450	230x140x10	450	700	70/90	II	Ø 515	580	780
SS5S - SS5SR	2,40	5	40x180	500	250x160x10	550	800	90/130	II	Ø 515	640	840
SS5E - SS5ER	2,40	5	40x200	500	470/390x160x10	600	820	135/170	II	Ø 515	750	950
SS7N - SS7NR	3,10	7	40x180	450	270x160x10	550	800	140/170	II	Ø 515	930	1150
SS7S - SS7SR	3,20	7	40x200	470	540/320x160x10	600	820	170/200	II	Ø 515	1420	1650
SS9S - SS9SR	4,20	9	40x200	470	540/320x160x10	650	870	270/300	III	Ø 600	1820	2100
SS11S - SS11SR	5,60	11	40x200	520	540/320x180x10	650	870	300/350	III	Ø 600	2100	3000



### V-SHAPE SUBSOILERS



Gascón International  
 Herederos de Manuel Gascón S.L.  
 Tel. +34-974-21 87 20  
 Fax. +34-974-21 87 21

[info@gasconinternational.com](mailto:info@gasconinternational.com)

INTERNATIONAL OFFICES  
 Tel. +34-689 82 30 51  
 Tel.Fax. +34-93-783 87 93  
[export@gasconinternational.com](mailto:export@gasconinternational.com)